

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 22.06.2022

Version number 1

Revision Date 22.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: EpoKwick FC Hardener**
- **Article number: AGB8198H**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the preparation: Hardener**
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier.**
Agar Scientific Ltd
Parsonage Lane
Stansted CM24 8GF
United Kingdom
sales@agarscientific.com
Tel: +44 (0) 1279 813 519
- **Further information obtainable from: Technical Support**
- **1.4 Emergency telephone number: 24 hours: +44 (0)1856 407333**

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS05 GHS06

- **Signal word Danger**
- **Hazard-determining components of labelling:**
2,2'-Iminodiethylamine

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 22.06.2022

Version number 1

Revision Date 22.06.2022

Trade name: EpoKwick FC Hardener

(Contd. of page 1)

Oxirane polymer
 Poly[oxy(methyl-1,2-etha
 nediyl)],
 .alpha.-hydro-.omega.-(2- aminomethylethoxy)-, ether with
 2-ethyl-2-(hydroxymethyl)
 -1,3-propanediol (3:1)

Hazard statements

H302 Harmful if swallowed.
 H331 Toxic if inhaled.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read carefully and follow all instructions.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.
 P321 Specific treatment (see on this label).
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 28063-82-3	Oxirane polymer ⚠ Eye Dam. 1, H318	>60.0%
CAS: 111-40-0 EINECS: 203-865-4	2,2'-Iminodiethylamine ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	<30.0%
CAS: 39423-51-3	Poly[oxy(methyl-1,2-etha nediyl)], .alpha.-hydro-.omega.-(2- aminomethylethoxy)-, ether with 2-ethyl-2-(hydroxymethyl) -1,3-propanediol (3:1) ⚠ Skin Corr. 1A, H314; Eye Dam. 1, H318; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312	5-15%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures
General information:

Immediately remove any clothing soiled by the product.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 22.06.2022

Version number 1

Revision Date 22.06.2022

Trade name: EpoKwick FC Hardener
(Contd. of page 2)

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing equipment only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· **After inhalation:**

Supply fresh air or oxygen; call for doctor.

No adverse effects are anticipated from inhalation.

· **After skin contact:** Wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

· **5.2 Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

· **5.3 Advice for firefighters**

· **Protective equipment:** Positive pressure self-contained breathing apparatus.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear gloves.

Wear protective gloves and glasses.

· **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about fire - and explosion protection:**

Extinguishing media: Water fog - dried resin only.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 22.06.2022

Version number 1

Revision Date 22.06.2022

Trade name: EpoKwick FC Hardener

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

111-40-0 2,2'-Iminodiethylamine

WEL	Long-term value: 4.3 mg/m ³ , 1 ppm
Sk	

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the eyes.
 Avoid contact with the eyes and skin.
- **Respiratory protection:**
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 22.06.2022

Version number 1

Revision Date 22.06.2022

Trade name: EpoKwick FC Hardener

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

 · **9.1 Information on basic physical and chemical properties**

· General Information

· Appearance:

Form:	Liquid
Colour:	Clear
· Odour:	Amine-like
· Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	>200 °C

· Flash point: >100 °C

· Flammability (solid, gas): Not applicable.

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower:	1 Vol %
Upper:	10 Vol %

· Vapour pressure at 20 °C: 0.5 hPa

· Density: Not determined.

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

· Solvent content:

VOC (EC) 0.00 %

Solids content: <10.0 %

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 22.06.2022

Version number 1

Revision Date 22.06.2022

Trade name: EpoKwick FC Hardener

(Contd. of page 5)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

- **Acute toxicity**
Harmful if swallowed.
Toxic if inhaled.

· LD/LC50 values relevant for classification:

111-40-0 2,2'-Iminodiethylamine

Oral	LD50	1,080 mg/kg (rat)
Dermal	LD50	1,090 mg/kg (rabbit)
Inhalative	LC50/4 h	1.8 mg/l (rat)

- **Specific symptoms in biological assay:**
- **Skin corrosion/irritation**
Causes severe skin burns and eye damage.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 22.06.2022

Version number 1

Revision Date 22.06.2022


Trade name: EpoKwick FC Hardener
(Contd. of page 6)

- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|--|---|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA | UN2735 |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG, IATA | 2735 AMINES, LIQUID, CORROSIVE, N.O.S. mixture
AMINES, LIQUID, CORROSIVE, N.O.S. mixture |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG, IATA <div style="text-align: center; margin: 10px 0;">  </div> <ul style="list-style-type: none"> · Class · Label | 8 Corrosive substances.
8 |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA | III |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: | Not applicable. |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Segregation groups · Stowage Category · Stowage Code · Segregation Code | Warning: Corrosive substances.
80
F-A,S-B
Alkalis
A
SW2 Clear of living quarters.
SG35 Stow "separated from" SGG1-acids |
| <ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| <ul style="list-style-type: none"> · Transport/Additional information: | |
| <ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) | 1L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml |
| <ul style="list-style-type: none"> · Transport category · Tunnel restriction code | 2
E |

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 22.06.2022

Version number 1

Revision Date 22.06.2022

Trade name: EpoKwick FC Hardener

(Contd. of page 7)

<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<ul style="list-style-type: none"> · UN "Model Regulation": 	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. MIXTURE, 8, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category H2 ACUTE TOXIC**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 50 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge and should assist the user with the safe handling of this material when properly applied. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 H302 Harmful if swallowed.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H411 Toxic to aquatic life with long lasting effects.
- **Department issuing SDS:** Sales department
- **Contact:**
 sales@agarscientific.com
 Tel: +44 (0) 1279 813 519
- **Abbreviations and acronyms:**
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Acute Tox. 4: Acute toxicity – Category 4
 Acute Tox. 3: Acute toxicity – Category 3
 Skin Corr. 1A: Skin corrosion/irritation – Category 1A
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3