

Date Printed 21.06.2022

Version number 1

Revision Date 21.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Lacomit Varnish
- · Article number: AGG371, AGG371A
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the preparation: Epoxy resin hardener for use in microscopy.
- · 1.3 Details of the supplier of the safety data sheet
- · Supplier.

Agar Scientific Ltd Parsonage Lane Stansted CM24 8GF United Kingdom sales@agarscientific.com Tel: +44 (0) 1279 813 519

- · Further information obtainable from: Technical Support
- · 1.4 Emergency telephone number: 24 hours: +44 (0)1856 407333

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



skull and crossbones

Acute Tox. 2 H300 Fatal if swallowed.



Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02 GHS05 GHS06

· Signal word Danger

(Contd. on page 2)



Date Printed 21.06.2022 Version number 1 Revision Date 21.06.2022

Trade name: Lacomit Varnish

(Contd. of page 1)

· Hazard-determining components of labelling:

butan-1-ol

· Hazard statements

H225 Highly flammable liquid and vapour.

H300 Fatal if swallowed.
H315 Causes skin irritation.
H318 Causes serious eye damage.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P330 Rinse mouth.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 1330-20-7	xylene	45.0%
EINECS: 215-535-7	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 71-36-3	butan-1-ol	20.0%
EINECS: 200-751-6	♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	
CAS: 123-86-4	butyl acetate -norm	15.0%
EINECS: 204-658-1	♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	
CAS: 67-64-1	acetone	3.0%
EINECS: 200-662-2	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 107-98-2	1-methoxy-2-propanol	3.0%
EINECS: 203-539-1	♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	1

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

- After inhalation: No adverse effects are anticipated from inhalation.
- · After skin contact: Wash with water and soap and rinse thoroughly.

(Contd. on page 3)



Date Printed 21.06.2022 Version number 1 Revision Date 21.06.2022

Trade name: Lacomit Varnish

(Contd. of page 2)

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: Water fog dried resin only.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective gloves and glasses.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

The dried resin is combustible, similar to wood. Burning dry resin emits dense, black smoke. As latex, material is not combustible.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

GB



Date Printed 21.06.2022 Version number 1 Revision Date 21.06.2022

Trade name: Lacomit Varnish

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

71-36-3 butan-1-ol

WEL Short-term value: 154 mg/m³, 50 ppm

123-86-4 butyl acetate -norm

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk

Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore

(Contd. on page 5)



Date Printed 21.06.2022 Version number 1 Revision Date 21.06.2022

Trade name: Lacomit Varnish


(Contd. of page 4)

to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



	cal properties
9.1 Information on basic physical and o General Information Appearance:	chemical properties
Appearance. Form:	Fluid
Colour:	Light red
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : >100 °C
Flash point:	16 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	340 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	9.4 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C:	0.85821 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	86.0 %
Organic solvents:	

(Contd. on page 6)



Date Printed 21.06.2022 Version number 1 Revision Date 21.06.2022

Trade name: Lacomit Varnish

(Contd. of page 5)
Solids content: 14.0 %

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Fatal if swallowed.

· LD/LC50	· LD/LC50 values relevant for classification:		
1330-20-7	1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (rat)	
Dermal	LD50	2,000 mg/kg (rabbit)	
71-36-3 b	utan-1-ol		
Oral	LD50	790 mg/kg (rat)	
Dermal	LD50	3,400 mg/kg (rabbit)	
Inhalative	LC50/4 h	8,000 mg/l (rat)	

- Specific symptoms in biological assay:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)



Date Printed 21.06.2022 Version number 1 Revision Date 21.06.2022

Trade name: Lacomit Varnish

(Contd. of page 6)

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised. Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	SESTION		_	4		
	SECTION	14:	Iranspor	t ini	torma	non

14.1 UN-Number	
· ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name	
· ADR	1263 PAINT
· IMDG, IATA	PAINT
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	
EMS Number:	F-E, <u>S-E</u>
· Stowage Category	В
· 14.7 Transport in bulk according to Annex II	
of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2

(Contd. on page 8)



Date Printed 21.06.2022 Version number 1 **Revision Date 21.06.2022**

Trade name: Lacomit Varnish

	(Contd. of page 7)
· Tunnel restriction code	D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

H2 ACUTE TOXIC

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge and should assist the user with the safe handling of this material when properly applied. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

· Department issuing SDS: Sales department

Contact:

sales@agarscientific.com Tel: +44 (0) 1279 813 519

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

(Contd. on page 9)



Date Printed 21.06.2022 Version number 1 Revision Date 21.06.2022

Trade name: Lacomit Varnish

Acute Tox. 2: Acute toxicity – Category 2
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

** Data compared to the previous version altered.

(Contd. of page 8)