

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 21.06.2022

Version number 1

Revision Date 08.12.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Resin 609 Liquid**
- **Article number:** AGG6432
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the preparation:** Molding - Embedding
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier.**
Agar Scientific Ltd
Parsonage Lane
Stansted CM24 8GF
United Kingdom
sales@agarscientific.com
Tel: +44 (0) 1279 813 519
- **Further information obtainable from:** Technical Support
- **1.4 Emergency telephone number:** 24 hours: +44 (0)1856 407333

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H335 May cause respiratory irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
methyl methacrylate
tetramethylene dimethacrylate
- **Hazard statements**
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 21.06.2022

Version number 1

Revision Date 08.12.2021

Trade name: Resin 609 Liquid
(Contd. of page 1)
Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read carefully and follow all instructions.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

- **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 80-62-6	methyl methacrylate	75-90%
EINECS: 201-297-1	☠ Flam. Liq. 2, H225; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 2082-81-7	tetramethylene dimethacrylate	10-25%
EINECS: 218-218-1	⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- **General information:** Immediately remove any clothing soiled by the product.

After inhalation:

- Supply fresh air.
- No adverse effects are anticipated from inhalation.

- **After skin contact:** Wash with water and soap and rinse thoroughly.

After eye contact:

- Rinse opened eye under running water. If symptoms persist, consult a doctor.
- Remove contact lenses, if present and easy to do so.

- **After swallowing:** No not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

- Product based on methacrylates.

4.3 Indication of any immediate medical attention and special treatment needed

- No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- **Suitable extinguishing agents:** Carbon dioxide, Sand, Dry powder.

For safety reasons unsuitable extinguishing agents:

- Water with full jet
- Water

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 21.06.2022

Version number 1

Revision Date 08.12.2021

Trade name: **Resin 609 Liquid**

(Contd. of page 2)

- **5.2 Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective gloves and glasses.
Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during cleaning up. Ensure adequate ventilation.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Wear appropriate personal protective equipment. Keep unprotected persons away. Avoid contact with skin and eyes. Wash hands thoroughly after handling.
- **Information about fire - and explosion protection:**
The dried resin is combustible, similar to wood. Burning dry resin emits dense, black smoke. As latex, material is not combustible.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Store in a well-ventilated place.
Keep ignition sources away. Do not smoke.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

80-62-6 methyl methacrylate

WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm
-----	--

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 21.06.2022

Version number 1

Revision Date 08.12.2021

Trade name: Resin 609 Liquid

(Contd. of page 3)

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.
- **Respiratory protection:**
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**
 Solvent resistant gloves. Butyl rubber, Fluorocarbon rubber (viton), Nitrile, natural rubber.
- **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Liquid
Colour:	Colourless
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	100 °C
- **Flash point:** 10 °C

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 21.06.2022

Version number 1

Revision Date 08.12.2021

Trade name: Resin 609 Liquid
(Contd. of page 4)

· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	430 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
· Vapour pressure at 20 °C:	47 hPa
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC (EC)	0.00 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.
- **Additional information:**
If stored longer than recommended and/or above recommended temperature, product may polymerize generating heat.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

 · **LD/LC50 values relevant for classification:**
80-62-6 methyl methacrylate

Oral	LD50	7,872 mg/kg (rat)
------	------	-------------------

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 21.06.2022

Version number 1

Revision Date 08.12.2021

Trade name: **Resin 609 Liquid**

(Contd. of page 5)

- **Specific symptoms in biological assay:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Additional toxicological information:**
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Small quantities can be polymerized with the matching system components and the cured solid material can be disposed of with the regular garbage. Larger quantities must be disposed of following the regulations of local authorities.
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|---|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA | UN1247 |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR | 1247 METHYL METHACRYLATE MONOMER, STABILIZED solution |

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31


Date Printed 21.06.2022

Version number 1

Revision Date 08.12.2021

Trade name: Resin 609 Liquid

(Contd. of page 6)

· IMDG, IATA	METHYL METHACRYLATE MONOMER, STABILIZED solution
· 14.3 Transport hazard class(es) · ADR, IMDG, IATA	
	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category · Stowage Code	Warning: Flammable liquids. 33 F-E,S-D C SW1 Protected from sources of heat. SW2 Clear of living quarters.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED SOLUTION, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Date Printed 21.06.2022

Version number 1

Revision Date 08.12.2021

 Trade name: **Resin 609 Liquid**

(Contd. of page 7)

SECTION 16: Other information

This information is based on our present knowledge and should assist the user with the safe handling of this material when properly applied. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.

- **Department issuing SDS:** Sales department

- **Contact:**

- sales@agarscientific.com
- Tel: +44 (0) 1279 813 519

- **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- *** Data compared to the previous version altered.**

GB