

Date Printed 16.02.2022 Version number 1 **Revision Date 16.02.2022**

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

Trade name: Epoxy Resin 603.2 Hardener

· Article number: AGG6713

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the preparation: Resin

· 1.3 Details of the supplier of the safety data sheet

· Supplier.

Agar Scientific Ltd Parsonage Lane Stansted CM24 8GF United Kingdom sales@agarscientific.com Tel: +44 (0) 1279 813 519

· Further information obtainable from: Technical Support

· 1.4 Emergency telephone number: 24 hours: +44 (0)1856 407333

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



health hazard

Repr. 2 H361d Suspected of damaging the unborn child.



Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



H302 Harmful if swallowed. Acute Tox. 4 Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS05

GHS07 GHS08 GHS09



Date Printed 16.02.2022 Version number 1 **Revision Date 16.02.2022**

Trade name: Epoxy Resin 603.2 Hardener

(Contd. of page 1)

· Signal word Danger

· Hazard-determining components of labelling:

m-Phenylenebis(methylamine)

salicylic acid

H411

3,3,5-trimethylhexamethylene-diamine

Polyoxypropylenediamine

Hazard statements

H302+H332 Harmful if swallowed or if inhaled.

H314 Causes severe skin burns and eye damage. May cause an allergic skin reaction. H317 Suspected of damaging the unborn child. H361d Toxic to aquatic life with long lasting effects.

Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

Read carefully and follow all instructions. P103

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor. P310

Specific treatment (see on this label). P321

P362+P364 Take off contaminated clothing and wash it before reuse.

Store locked up. P405

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description**: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 1477-55-0	m-Phenylenebis(methylamine)	10-25%	
EINECS: 216-032-5	Acute Tox. 3, H331; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412		
CAS: 25513-64-8	3,3,5-trimethylhexamethylene-diamine	10-25%	
	Skin Corr. 1B, H314; Eye Dam. 1, H318;		
CAS: 69-72-7	salicylic acid	2.5-10%	
EINECS: 200-712-3	🕸 Repr. 2, H361d; 📀 Eye Dam. 1, H318; 🗘 Acute Tox. 4, H302		
CAS: 9046-10-0	Polyoxypropylenediamine	2.5-10%	
	♦ Skin Corr. 1B, H314		

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

(Contd. on page 3)



Date Printed 16.02.2022 Version number 1 Revision Date 16.02.2022

Trade name: Epoxy Resin 603.2 Hardener

(Contd. of page 2)

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air.

No adverse effects are anticipated from inhalation.

- · After skin contact: Wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- 5.3 Advice for firefighters
- · **Protective equipment:** Positive pressure self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear gloves.

Wear protective gloves and glasses.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Extinguishing media: Water fog - dried resin only.

(Contd. on page 4)



Date Printed 16.02.2022 Version number 1 Revision Date 16.02.2022

Trade name: Epoxy Resin 603.2 Hardener

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles



Date Printed 16.02.2022 Version number 1 Revision Date 16.02.2022

Trade name: Epoxy Resin 603.2 Hardener

(Contd. of page 4)

9.1 Information on basic physical and	chemical properties
General Information	
Appearance:	Limita
Form: Colour:	Liquid Yellowish
Odour:	Amine-like
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	∍: 274 °C
Flash point:	134 °C
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure at 25 °C:	~0 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Fully miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
VOC (EC)	0.00 %
Calida cantonti	12.5-35 %
Solids content:	12.0-00 /0

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)



Date Printed 16.02.2022 Version number 1 Revision Date 16.02.2022

Trade name: Epoxy Resin 603.2 Hardener

(Contd. of page 5)

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if swallowed or if inhaled.

· LD/LC50 values relevant for classification:

1477-55-0 m-Phenylenebis(methylamine)

Oral LD50 1,040 mg/kg (rat) Inhalative LC50/4 h 2.4 mg/l (rat)

- · Specific symptoms in biological assay:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity

Suspected of damaging the unborn child.

- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

ЗВ



Date Printed 16.02.2022 Version number 1 Revision Date 16.02.2022

Trade name: Epoxy Resin 603.2 Hardener

(Contd. of page 6)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage

- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN2735
· 14.2 UN proper shipping name · ADR	2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m Phenylenebis (methylamine) Polyoxypropylenediamine), ENVIRONMENTALLY HAZARDOUS
· IMDG, IATA	AMINES, LIQUID, CORROSIVE, N.O.S. (m Phenylenebis (methylamine) Polyoxypropylenediamine)
· 14.3 Transport hazard class(es)	
ADR	
· Class · Label	8 Corrosive substances. 8
· IMDG, IATA	
W. D.	
· Class	8 Corrosive substances.
· Label	8
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user · Hazard identification number (Kemler code	
· EMS Number: · Segregation groups	F-A,S-B Alkalis
· Stowage Category	A
· Segregation Code	SG35 Stow "separated from" SGG1-acids
14.7 Transport in bulk according to Annex	
of Marpol and the IBC Code	Not applicable.

(Contd. on page 8)



Date Printed 16.02.2022 Version number 1 Revision Date 16.02.2022

Trade name: Epoxy Resin 603.2 Hardener

	(Contd. of page 7
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
,	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (M-PHENYLENEBIS (METHYLAMINE), POLYOXYPROPYLENEDIAMINE), 8, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge and should assist the user with the safe handling of this material when properly applied. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H331 Toxic if inhaled.
- H361d Suspected of damaging the unborn child.
- H412 Harmful to aquatic life with long lasting effects.
- Department issuing SDS: Sales department
- Contact:

sales@agarscientific.com Tel: +44 (0) 1279 813 519

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)



Date Printed 16.02.2022

Version number 1

Revision Date 16.02.2022

Trade name: Epoxy Resin 603.2 Hardener

(Contd. of page 8)

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1
Repr. 2: Reproductive toxicity – Category 2
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3